The Charger PROOH₂O Series



WATER TREATMENT SYSTEMS

Capacity is one of the first things you should look for in a water treatment system. The average family uses 80 to 100 gallons of water per person per day. That means a household of five requires 400 gallons of softened water daily.



How a WS1 Hi-Flow System Softens Water

Hard water passes through the media tank that contains resin beads coated with sodium ions. The calcium and magnesium ions are exchanged for sodium (or potassium) ions, thus softening the water. When the beads have trapped the hardness and need to be regenerated, the Hi-Flow's control valve charges them with the brine from the brine tank.

As regeneration occurs, calcium and magnesium (hardness) ions are freed from the beads, replaced with sodium or potassium ions; and the system is ready to soften water again. Pro H2O Water Treatment Systems Feature:

- Up to six fully adjustable cycles
- Certified flow rates to 27 gpm
- Operating pressure to 125 psi
- Operating temperatures to 110°F
- Metered (DIR) or timed regeneration

Brine tank performance insurance All Charger water softeners may be ordered with optional salt grid which virtually prevents salt bridging.

Demand Initiated Regeneration (DIR) Save water and up to 40% in salt usage by adding meter-controlled regeneration to your unit.

> WS1 HI-FLOW SERIES

Your **Charger** Water Treatment Dealer:

chargerwater.com





Clack WS1 1" Hi-Flow Metered Valve

March 1				
Model #	Grain Capacity	Mineral Tank	Brine Tank	SVC Flow
Cabinet Model	s with 1" Turbul	ator Backwash		
CWWS116TC	16,000	8 X 35	13.5 X 22.5	11.0
CWWS124TC	24,000	9 X 35	13.5 X 22.5	12.0
CWWS132TC	32,000	10 X 35	13.5 X 22.5	13.0
CWWS140TC	40,000	12 X 35	13.5 X 22.5	13.4
Cabinet Model	s with 1" Stando	ard Distributor		
CWWS116RC	16,000	8 X 35	13.5 X 22.5	11.0
CWWS124RC	24,000	9 X 35	13.5 X 22.5	12.0
CWWS132RC	32,000	10 X 35	13.5 X 22.5	13.0
CWWS140RC	40,000	12 X 35	13.5 X 22.5	13.4
	with 1" Turbula			
CWWS116T	16,000	7 X 44	15 X 17	11.0
CWWS124T	24,000	7 X 44	15 X 17	11.0
CWWS132T	32,000	8 X 44	15 X 17	12.0
CWWS140T	40,000	9 X 48	15 X 17	13.0
CWWS148T	48,000	10 X 44	15 X 17	13.4
CWWS164T	64,000	10 X 54	15 X 17	14.6
CWWS180T	80,000	12 X 48	15 X 17	14.9
2 Tank Models with 1" Standard Distributor				
CWWS116R	16,000	7 X 44	15 X 17	11.0
CWWS124R	24,000	8 X 44	15 X 17	11.0
CWWS132R	32,000	9 X 48	15 X 17	12.0
CWWS140R	40,000	10 X 44	15 X 17	13.0
CWWS148R	48,000	10 X 54	15 X 17	14.6
CWWS164R	64,000	12 X 52	15 X 17	14.9
CWWS180R	80,000	13 X 54	15 X 17	15.0



chargerwater.com